

Interferometric Detection of Freeze-Thaw Displacements of Alaskan Permafrost Using ERS-1

Paul A. Rosen and Andrew K. Gabriel
Jet Propulsion Laboratory, California Institute of Technology
4800 Oak Grove Drive, Pasadena, California 91109

Charles L. Werner
Remote Sensing Laboratories, Department of Geography
University of Zurich - Irchel, Winterthurerstrasse 190
CH-8057 Zürich, Switzerland

The possibility of making large scale (50 km) measurements of motions of the earth's surface with high resolution (10 m) and very high accuracy (1 cm) from multipass SAR interferometry was recently established [1]. Other experiments [2, 3] have confirmed the viability and usefulness of the method, some dramatically [4, 5]. Work is underway in the present study to measure displacements from the freeze-thaw cycles in Alaskan permafrost. The ground is known to move significantly in these cycles, and providing that freezing does not cause image decorrelation, it should be possible to measure both ground swelling and subsidence.

We have obtained data of multiple passes of ERS-1 over the Toolik Lake region of northern Alaska of suitable quality for interferometry. The data were processed at the Alaska SAR Facility into images. From these data, pairwise image registration offsets were measured as previously described [6]. Single interferograms were formed after oversampling the data by a factor of two. Spectral shift filtering [7] to reduce baseline decorrelation was applied where the baseline was large. Phase unwrapping was performed, and the multipass baselines were estimated from the images using both orbit ephemerides and scene tie points. Convergence of the orbits was modelled in the baseline estimation by a linear dependence of the baseline on the along track position. The phases were scaled by the baseline ratio, and double-difference interferograms (DDI) were formed.

The data were acquired over a 2 month period in the autumn of 1991; evidence of transitions from thaw to freeze should be present in the DDIs phase measurements. Indeed, the DDIs examined so far show significant phase changes over the period of the observation.

"Mapping small elevation changes over large areas: Differential radar interferometry," *J. Geophys. Res.* 94, 9183-9191, 1989.

- [2] R. M. Goldstein, "Glacier motion from interferometry," *Third Spaceborne Imaging Radar Symposium* Jan. 18-21, 1993, Jet Propulsion Laboratory, CA.
- [3] S. N. Coulson, "Bonn experiment on differential interferometry," *Proc. of CEOS Working Group*, Dec. 7-9, 1992, Pasadena CA.
- [4] D. Massonet *et al.*, "The displacement field of the Landers earthquake mapped by radar interferometry," *Nature*, 364, no. 6433, 138-142, 1993.
- [5] H. A. Zebker *et al.*, "On the derivation of coseismic displacement fields using differential radar interferometry: the Landers earthquake," submitted to *J. Geophys. Res.*, Dec. 1, 1993
- [6] H. A. Zebker *et al.*, "Accuracy of topographic maps derived from ERS-1 interferometric radar," submitted to *IEEE Trans. Geosci. Rem. Sens.*, March, 1993.
- [7] F. A. Gatelli *et al.*, "Use of spectral shift in SAR interferometry: applications to ERS-1," submitted to *IEEE Trans. Geosci. Rem. Sens.*, 1993.

References

- [1] A. K. Gabriel, R. M. Goldstein, and H. A. Zebker,